

Marked Up Version Of The Pending Claims under 37 C.F.R. 1.121(c)(1)(ii):

Amend claims 40-53, 60-85 and 86-124 as follows and in accordance with
37 C.F.R. 1.121(c), by which the Applicant submits the following marked up
version:

1-39. (previously canceled without prejudice)

40-53. (canceled without prejudice)

54-59. (previously canceled without prejudice)

60-85. (canceled without prejudice)

86. (new) A bridge tailpiece having an element to receive at least one musical
instrument string, the element comprising:

a first string anchoring point for each string; and
an alternate string anchoring point for each string.

87. (new) The bridge tailpiece of claim 86, wherein the bridge tailpiece further
comprises:

a tremolo.

88. (new) The bridge tailpiece of claim 86, wherein the bridge tailpiece further
comprises:

a fulcrum tremolo.

1 89. (new) A bridge tailpiece with a forward end and a rearward end and upper portion
2 and a lower portion, comprising:

3 an upper portion comprising:

4 a base;

5 a bridge element connected to the base, the bridge element located closer
6 to the forward end forming a second critical point; and

7 a first portion connected to the base and located in the rearward end
8 forming an alternate string anchoring point closer to the lower
9 portion than the second critical point, and

10 wherein the lower portion being attached to the upper portion and the lower
11 portion comprises:

12 a second portion that is transverse to the alternate string anchoring point;

13 and

14 a first string anchoring point.

15 90. (new) The bridge tailpiece of claim 89, wherein the bridge tailpiece further
16 comprises:

17 a fulcrum tremolo.

18 91. (new) The bridge tailpiece of claim 89, wherein the upper portion
19 further comprises:

20 a string opening located between the first anchoring point and the second critical
21 point, and

22 wherein the second portion further comprises:

23 a member with a string passageway connected to the second anchoring
24 point having an axis, the axis being aligned to the string opening in
25 upper portion.

92. (new) The bridge tailpiece of claim 91, wherein the bridge tailpiece further comprises:

a fulcrum tremolo.

93. (new) A stringed musical instrument comprising:

a body having a surface;

a bridge element attached to the body; and

a tailpiece element attached to the surface of the body, the tailpiece comprising:

a first portion having a rearward surface having a string anchoring point formed therein, and located above the surface of the body; and

a second portion that is transverse to the first portion, and extends through at least a portion of the body, the second portion comprising:

a first end that connects the second portion to the first portion;

a second end, the second end having an alternate string anchoring point and formed therein below the surface of the body; and

an elongated passageway that extends through the second portion from the first end to the second end, along a longitudinal axis of the second portion, forming at least one opening on each end.

94. (new) An apparatus comprising:

a body;

a fulcrum tremolo;

a biasing element comprising a first end connected to the fulcrum tremolo and a second end connected to the body; and

a singular apparatus connected to the fulcrum tremolo, the singular apparatus comprising:

a thumbwheel operable to position a spring holder,

wherein rotation of the thumbwheel adjusts the tension of the biasing element.

1 95. (new) The apparatus of claim 94, wherein the biasing element further comprises:
2 a U-shaped spring.

3 96. (new) An apparatus comprising:
4 a body; and
5 a fulcrum tremolo comprising:

6 a biasing element comprising a first end and a second end, the first end
7 and the second end positioned opposite from each other on the
8 biasing element, the biasing element positioned between the
9 fulcrum tremolo and the body;

10 a spring holder connected to the first end of the biasing element and
11 having a threaded portion;

12 a singular apparatus comprising a thumbwheel, the thumbwheel
13 comprising a threaded portion; and

14 a threaded elongated portion, the threaded elongated portion threadedly
15 connected to the spring holder and the threaded elongated portion
16 threadedly connected to the singular apparatus,

17 wherein rotation of the thumbwheel adjusts the tension of the biasing element
18 and thereby adjusting a position of a rotation of a fulcrum tremolo.

19 97. (new) The apparatus of claim 96, wherein the thumbwheel holder further
20 comprises:

21 a secondary spring holder being threadedly engaged with the threaded elongated
22 portion, and

23 wherein the fulcrum tremolo being positioned between the thumbwheel and the
24 secondary spring holder.

25 98. (new) The apparatus of claim 96, wherein the spring holder being positioned
between the thumbwheel and the biasing element.

1 99. (new) The apparatus of claim 98, further comprising a secondary spring holder
2 connected to the biasing element,

3 wherein the thumbwheel further comprises a second elongated threaded portion,
4 wherein the fulcrum tremolo further comprises a threaded opening, and
5 wherein the thumbwheel is positioned between the secondary spring holder and
6 the threaded opening.

7 100. (new) An apparatus comprising:

8 a body;

9 a fulcrum tremolo coupled to the body through a pivot axis; and

10 an additional apparatus coupled to the fulcrum tremolo and the body, the

11 additional apparatus comprising a thumbwheel to the adjust position of

12 fulcrum tremolo about the fulcrum tremolo.

13 101. (new) An apparatus of a stringed musical instrument comprising:

14 at least one second critical point; and

15 a single piece of stamped material comprising:

16 a base plate being approximately planar comprising at least one tier for

17 displacing the at least one second critical point from the base plate.

18 102. (new) The apparatus of claim 101, wherein the apparatus further comprises:

19 at least one string anchor portion operable to anchor an end of a string.

103. (new) The apparatus of claim 101, wherein the apparatus further comprises:
a second critical point attached to the single piece of stamped material, and
wherein the base plate further comprises:
a forward edge, a portion of the forward edge being a pivot and forming a
pivot axis, and
an end opposite of the forward edge, and
wherein the single piece of stamped material further comprises:
a bend in the single piece of stamped material at an opposite end of the
forward edge of the base plate;
at least one string socket to receive an end of a string; and
a transverse portion comprising:
at least one spring socket to receive an end of at least one biasing
spring; and
wherein the bend transitions the base plate to the transverse portion and
the bend and the transverse portion are approximately parallel to
the pivot axis.
104. (new) A fulcrum tremolo comprising an intonation module with a forward portion
and a rearward portion:
the intonation module comprising:
a base;
a bridge element connected to the base, the bridge element located closer
to the forward end forming a second critical point; and
wherein the rearward portion forms a string anchoring point closer to the
base than the second critical point; and
wherein the string anchoring point is located a critical distance from the
second critical point operable to render a string as approximately
inextensible between the anchoring point and the second critical
point.

105. (new) The fulcrum tremolo of claim 104, wherein the intonation further comprises:

a macro tuner.

106. (new) The fulcrum tremolo of claim 104, wherein the critical distance is at least 0.25 inch.

107. (new) The fulcrum tremolo of claim 104, wherein the critical distance is about equal to the length of conventional musical instrument string wrapping.

108. (new) The fulcrum tremolo of claim 104, wherein the intonation module further comprises:

a macro tuner.

109. (new) The fulcrum tremolo of claim 104, further comprising:
a base plate attached to the intonation module, the base plate comprising a string hole.

110. (new) A fulcrum tremolo with a forward end and a rearward end, the fulcrum tremolo comprising:

- a base plate comprising a string hole,
- a spring holder that is transverse to the base plate and attached to the base plate comprising:
 - a first string anchoring point; and
 - a string passageway having an axis wherein a longitudinal axis of the string passageway aligns with the string hole;
- an intonation module attached to the spring holder comprising:
 - a base;
 - a bridge element connected to the base, the bridge element located closer to the forward end than the rearward end and forming a second critical point; and

wherein the rearward portion forms an alternate string anchoring point closer to the base than the second critical point; and

wherein the alternate string anchoring point is located a critical distance from the second critical point so that a string is rendered essentially inextensible between the alternate string anchoring point and the second critical point.

111. (new) The fulcrum tremolo of claim 110, wherein the intonation module further comprises:

- a macro tuner.

112. (new) A tremolo for a stringed musical instrument comprising:
at least one support element; and
a unitary component that is a single piece of bent material comprising:
a base plate being approximately planar, comprising:
a forward edge, a portion of the forward edge being a pivot and
forming a pivot axis, and
an end opposite of the forward edge;
a bend in the unitary component at an opposite end of the forward edge of
the base plate;
a transverse portion comprising:
at least one spring socket to receive an end of at least one biasing
element; and
at least one string socket formed in the single piece of bent material to
receive an anchor of a string,
wherein the bend transitions the base plate to the transverse portion, and
wherein the bend and the transverse portion are approximately parallel to
the pivot axis, and
wherein the unitary component is connected to the at least one support
element.

113. (new) The tremolo of claim 112, wherein the transverse portion further
comprises:
the at least one string socket.

114. (new) A fulcrum tremolo for a stringed musical instrument comprising:
a unitary component that is a single piece of bent material comprising:
a base plate being approximately planar, comprising:
a forward edge, a portion of the forward edge being a pivot and
forming a pivot axis, and
an end opposite of the forward edge;
a first bend in the unitary component at an opposite end of the forward
edge of the base plate;
at least one string socket to receive an end of a string; and
a transverse portion comprising:
at least one spring socket to receive an end of at least one biasing
element,
wherein the first bend transitions the base plate to the transverse portion,
and
wherein the first bend and the transverse portion are approximately
parallel to the pivot axis,
a second critical point connected to the unitary component.

115. (new) The fulcrum tremolo of claim 114, wherein the first bend further
comprises:
a reinforcement.

116. (new) The fulcrum tremolo of claim 114, wherein the transverse portion further
comprises:
a spring blade.

- 1 117. (new) The fulcrum tremolo of claim 116, wherein the base plate further
2 comprises at least one string hole, and
3 wherein the spring blade further comprises:
4 an upper portion;
5 a lower portion comprising at least one string passageway, each of the at
6 least one string passageway is aligned with at least one of the least
7 one string hole in the base plate; and
8 a second bend that transitions from the upper portion to the lower portion,
9 wherein the lower portion being bent transverse the upper portion.
- 10 118. (new) The fulcrum tremolo of claim 116, wherein the transverse portion further
11 comprises:
12 at least one tier for displacing the at least one second critical point from the base
13 plate.
- 14 119. (new) The fulcrum tremolo of claim 114, wherein the transverse portion further
15 comprises:
16 the at least one string socket.
- 17 120. (new) The fulcrum tremolo of claim 114, wherein the pivot further comprises:
18 a pivot having a knife edge.
- 19 121. (new) The fulcrum tremolo of claim 114, wherein the pivot further comprises:
20 a pivot having a beveled edge.
- 21 122. (new) The fulcrum tremolo of claim 114, wherein the pivot further comprises:
22 at least a portion of a bearing surface.
- 23 123. (new) The fulcrum tremolo of claim 114, wherein the pivot further comprises:
24 at least a portion of a ball bearing surface; and
25 at least a portion of a shaft.

1 124. (new) The fulcrum tremolo of claim 114, wherein the pivot further comprises:
2 a plurality of ring bearings.
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25